



DNSSEC Deployment a case study

Olaf M. Kolkman

Olaf@NLnetLabs.nl

RIPE NCCs Project Team:

Katie Petrusha, Brett Carr, Cagri Coltekin, Adrian Bedford,
Arno Meulenkamp, and Henk Uijterwaal

Presentation roadmap

- Overview of problem space
 - DNSSEC introduction
 - Architectural changes to allow for DNSSEC deployment
- Deployment tasks
 - Key maintenance
 - DNS infrastructure
 - Providing secure delegations



Why DNSSEC

- Good security is multi-leveled
 - Multiple defense rings in physical secured systems

10000100101001010110000010111000010000001111100000
110101110010101101100101100110010111101100000
1001110101111111000011101101000011111011000
11111101010000111101010100100100111110110000
1001010010111000001101000010000001000000000
10000111011010011101001011011000010100000
010001011011001010100001000100010000000000
0000111101001010110001111110100000000000
0001010110100011001100001100110000110011000
0010111001001001100
010010100100001110
100100101000111110
0110001011100111
1101101011101111
10001011001010010
01000111001001001
0111011011001100
1110010000011000
010111100000000
001101010100000
001010100000000
111111000000000
101100000000000
101100000000000



Bourtonne, source Wikipedia



Why DNSSEC

- Good security is multi-leveled
 - Multiple defense rings in physical secured systems
 - Multiple ‘layers’ in the networking world
- DNS infrastructure
 - Providing DNSSEC to raise the barrier for DNS based attacks
 - Provides a security ‘ring’ around many systems and applications




DNSSEC evangelist of the day

- NLnet Labs (www.NLnetLabs.nl)
 - Not for profit Open Source Software lab
 - NSD, open source nameserver
 - DNS and DNSSEC research
 - Protocol and software development
 - Deployment engineering
- Co-Chair of the IETF DNSEXT working group

The Problem

- DNS data published by the registry is being replaced on its path between the “server” and the “client”.
- This can happen in multiple places in the DNS architecture
 - Some places are more vulnerable to attacks than others
 - Vulnerabilities in DNS software make attacks easier (and there will always be software vulnerabilities)


DNS Architecture




Provisioning

DNS Protocol


DNS Architecture



Example: Unauthorized mail scanning



Example: Unauthorized mail scanning



Targets...

Where do DNS and economics meet?

- SPF, DomainKey and family
 - Technologies that use the DNS to mitigate spam and phishing: \$\$\$ value for the black hats
- Stock tickers, RSS feeds
 - Usually no source authentication but supplying false stock information via a stock ticker and via a news feed can have \$\$\$ value
- ENUM
 - Mapping telephone numbers to services in the DNS



DNSSEC properties

- DNSSEC provides message authentication and integrity verification through cryptographic signatures
 - Authentic DNS source
 - No modifications between signing and validation
- It does not provide authorization
- It does not provide confidentiality



Metaphor

- Compare DNSSEC to a sealed transparent envelope.
- The seal is applied by whoever closes the envelope
- Anybody can read the message
- The seal is applied to the envelope, not to the message

nlnetlabs.nl.
nlnetlabs.nl.
nlnetlabs.nl.

86400 IN NS omval.tednet.nl.

86400 IN **RRSIG** NS 5 2 86400 20060131005003 (
20060101005003 43791 nlnetlabs.nl.
y9URn7lLgXdPh2MY/I/CRkmG5PZ2nJQxndGHwSB8OP15
[...]
Qgl+b00j54b/65TyYVqPp3CLVt/q6L67SMK9orE=)

nlnetlabs.nl.

86400 IN **DNSKEY** 257 3 5 (
AQPzzTWMz8qSWIqlfRnPckx2BiVmkVN6LPupO3mbz7Fh
[...]
9QP7y2bVw5zSbFCrefk8qCUBgfHm9bHzMG1UBytEIQ==
) ; key id = 43791

nlnetlabs.nl.

86400 IN **RRSIG** DNSKEY 5 2 86400 20060131005003 (
20060101005003 43791 nlnetlabs.nl.
6mEWVaFKLQrypCJb0wgzW56UC1SVGYW3z+KJVM/uANnA
[...]
4cCBqAX/mE2N5nUZians0/IT1TzuqVS5h12R2jE=)

open.nlnetlabs.nl.

86400 IN **RRSIG** A 5 3 86400 20060131005003 (
20060101005003 43791 nlnetlabs.nl.
ZoZl6om+q5e4jrrDB64mMXpiloCQVe6NDu7KZbv7k9fg
[...]
t+Xc4iQPI+HTPn5A18pjaEA9KAK7NFLTZHz5uV8=)

open.nlnetlabs.nl.


86400 IN **RRSIG** AAAA 5 3 86400 20060131005003 (
20060101005003 43791 nlnetlabs.nl.
[...]

Presentation roadmap

- Overview of problem space
 - DNSSEC introduction
 - Architectural changes to allow for DNSSEC deployment
- Deployment tasks
 - Key maintenance
 - DNS infrastructure
 - Providing secure delegations

DNSSEC

Architecture modifications




DNSSEC deployment tasks

- Key maintenance policies and tools
 - Private Key use and protection
 - Public key distribution
- Zone signing and integration into the provisioning chain
- DNS server infrastructure
- Secure delegation registry changes
 - Interfacing with customers

Presentation roadmap

- Overview of problem space
 - DNSSEC introduction
 - Architectural changes to allow for DNSSEC deployment
- Deployment tasks
 - Key maintenance
 - DNS server infrastructure
 - Providing secure delegations





Key Maintenance

- DNSSEC is based on public key cryptography
 - Data is signed using a private key
 - It is validated using a public key

Operational problems:

- Dissemination of the public key
- Private key has a '*best before*' date
 - Keys change, and the change has to disseminate



Public Key Dissemination

- In theory only one trust-anchor needed that of the root
 - How does the root key get to the end user?
 - How is it rolled?
- In absence of hierarchy there will be many trust-anchors
 - How do these get to the end-users?
 - How are these rolled?
- These are open questions, making early deployment difficult.



Public Key Dissemination at RIPE NCC


In absence of a signed parent zone and automatic rollover:

- Trust anchors are published on an “HTTPS” secured website
- Trust anchors are signed with the RIPE NCC public keys
- Trust anchor will be rolled twice a year (during early deployment)
- Announcements and publications are always signed by x.509 or PGP

Key Management

- There are many keys to maintain
 - Keys are used on a per zone basis
 - Key Signing Keys and Zone Signing Keys
 - During key rollovers there are multiple keys
 - In order to maintain consistency with cached DNS data [draft-ietf-dnsop-dnssec-operational-practices]
- Private keys need shielding


Private Key Maintenance





Maintaining Keys and Signing Zones

- The KeyDB maintains the private keys
 - It ‘knows’ rollover scenarios
 - UI that can create, delete, roll keys without access to the key material
 - Physically secured
- The signer ties the Key DB to a zone
 - Inserts the appropriate DNSKEYs
 - Signs the the zone with appropriate keys
- Strong authentication





Private Key Maintenance

The software

- Perl front-end to the BIND dnssec-signzone and dnssec-keygen tools
- Key pairs are kept on disc in the “BIND format”
- Attribute files containing human readable information
 - One can always bail out and sign by hand.
- Works in the RIPE NCC environment, is a little rough edged but available via the www.ripe.net/disi

Example session

```
$ maintkeydb create KSK RSASHA1 2048 example.net
```

```
Created 1 key for example.net
```

```
$ maintkeydb create ZSK RSASHA1 1024 example.net
```

```
Created 2 keys for example.net
```

```
$ dnssigner example.net
```

```
Output written to :example.net.signed
```

```
$ maintkeydb rollover zsk-stage1 RSASHA1 example.net
```


Presentation roadmap

- Overview of problem space

- DNSSEC introduction
- Architectural changes to allow deployment

- Deployment tasks

- Key maintenance
- DNS server infrastructure
- Providing secure delegations





Infrastructure


- One needs primary and secondary servers to be DNSSEC protocol aware
- We had a number of concerns about memory CPU and network load
 - Research done and published as RIPE 352
 - What follows are the highlights of that paper

Question

What would be the immediate and initial effect on memory, CPU and bandwidth resources if we were to deploy DNSSEC on RIPE NCC's 'primary' name server?

- Measure through simulation.
- Published in RIPE352

NSD 2.3.0 VSZ due to signing (FreeBSD 6.0)



Memory

- On ns-pri.ripe.net factor 4 increase.
 - From ca. 30MB to 150MB
 - No problem for a 1GB of memory machine
- On k.root-servers.net
 - Increase by ca 150KB
 - Total footprint 4.4 MB
- Nothing to worry about
- Memory consumption on authoritative servers can be calculated in advance.
 - No surprises necessary




Serving the zones

Query Properties

- DNS clients set the “DO” flag and request for DNSSEC data.
 - Not to do their own validation but to cache the DNSSEC data for.
- EDNS size determines maximum packet size.
(DNSSEC requires EDNS)
- EDNS/DO properties determine which fraction of the replies contain DNSSEC information

EDNS properties



```

1000010010100101011000001011100001000001111100000
1101011100101011011001011001100101110110001000
10011101011111111000111101101000111111011000
11111101010000111101010100100100111110110100
1001010010111000001101000010000001000000000000
1000011101101001110100101101100001010000000000
0100010110110010110100001000100010001000000000
000011101001101101110001111110100000000000000
000101011101000110011100011110100000000000000
001011100100100100010110110110110110110110110
010010011000011000001001000000000000000000000
100100100001111100101010100000000000000000000
011000101110011101001000000000000000000000000
1101101111011110111101101111011011110110111
100010110010001011000000000000000000000000000
010001110010010010010000000000000000000000000
011101101110011001100110011001100110011001100
111001100000111111111111111111111111111111111
010111110000111111111111111111111111111111111
001101010101010101010101010101010101010101010
001011010101010101010101010101010101010101010
111111010101010101010101010101010101010101010
101101010101010101010101010101010101010101010

```

trace server

ns-pri BIND 9.3.1

ns-pri BIND 9.3.1

k.root BIND 9.3.1

k.root BIND 9.3.1

k.root BIND 9.3.1

k.root NSD 2.3.0

k.root NSD 2.3.0

k.root NSD 2.3.0

CPU

ZSK size

WCPU

0000

ca 14%

2048

ca 18%

0000

ca 38%

2048

ca 42%

mod 2048

ca 50%

0000

ca 4%

2048


ca 4%

mod 2048

ca 5%

Bandwidth Factors

- fraction of queries with DO bit
 - Seen in difference between ns-pri and k.root result
 - Seen in difference between modified and unmodified servers
- Including DNSKEY RR in additional section.
 - Seen in difference between k.root traces from modified nsd and modified named
- Difference in answer patterns
 - Name Errors vs Positive answers
 - Difficult to asses from this data



Bandwidth Increase

- Significant for ns-pri.ripe.net
 - Well within provisioned specs.
- Insignificant for k.root-servers.net
 - Upper bound well within provisioning specs


(Key size influences bandwidth but bandwidth should not influence your key size)

Conclusion of these measurements

- CPU, Memory and Bandwidth usage increase are not prohibitive for deployment of DNSSEC on k.root-servers.net and ns-pri.ripe.net
- Bandwidth increase is caused by many factors
 - Hard to predict but fraction of DO bits in the queries is an important factor
- CPU impact is small, Memory impact can be calculated
- Don't add DNSKEY RR set in additional

Presentation roadmap

- Overview of problem space
 - DNSSEC introduction
 - Architectural changes to deployment
- Deployment tasks
 - Key maintenance
 - DNS server infrastructure
 - Providing secure delegations



Parent-Child Key Exchange

- In the DNS the parent signs the “Delegations Signer” RR
 - A pointer to the next key in the chain of trust

```
$ORIGIN net.  
  
kids NS    ns1.kids  
      DS    (...) 1234  
      RRSIG DS (...) net.  
  
money NS   ns1.money  
      DS    (...)   
      RRSIG DS (...) net.
```

```
$ORIGIN kids.net.  
  
@ NS     ns1  
  RRSIG NS (...) kids.net.  
  DNSKEY (...) (1234)  
  DNSKEY (...) (3456)  
  RRSIG dnskey ... 1234 kids.net.  
  RRSIG dnskey ... 3456 kids.net.  
  
beth A 127.0.10.1  
    RRSIG A (...) 3456 kids.net.
```

- DNSKEY or DS RR needs to be exchanged between parent and child

Underlying Ideas

- The DS exchange is the same process as the NS exchange
 - Same authentication/authorization model
 - Same vulnerabilities
 - More sensitive to mistakes
- Integrate the key exchange into existing interfaces
 - Customers are used to those
- Include checks on configuration errors
 - DNSSEC is picky
- Provide tools
 - To prevent errors and guide customers



How Did we Proceed

- The `ds-rdata:` attribute was added to the Domain object
- The zone generation tool:extract DS RRs from `ds-rdata:` attributes
- We introduced a filter, to block `ds-rdata:` for zones not yet signed
- Added a number of “DelChecker” checks

Integration issue

- Thinking about DNSSEC made the NCC look at the provisioning system as a whole
 - Prompted a couple of modifications
 - Zone generation (generation of zone now from the Whois DB)
 - Authentication model (introduction of mnt-domain)
 - Possible replay attacks (countered by using timestamps of the strong auth. mechanisms)
- All these issues are NOT DNSSEC specific
- Addressed over the last 2 years



Introducing the Web Interface

- Eases registration of keys and the rollovers
 - Can also be used for “classic” delegations
- Restricts user somewhat
 - Fewer degrees of freedom mean fewer errors
 - One can always manually create the Domain object
- Version 1 to appear shortly
 - Demo in the hallway



Web Interface Examples


May the Demo Gods be with us.

We'll cheat.

NCC Roadmap

- RIPE NCC is signing its zones
 - Forward zones (ripe.net &c) are signed
 - Signatures are still being introduced in reverse zones (v4 and v6)
- Secure Delegations available for a number of /8 equivalent zones
- Policy and procedures available
 - www.ripe.net/reverse

QUESTIONS?



Acknowledgements: A number of these slides are based on earlier work at RIPE NCC.