

A Tour of UNIX

...looking a bit closer under the
hood



Processes

- A running instance of a program is called a "process"
- Identified by a numeric process id (pid)
 - Pid is unique while process is running; will be re-used some time after it terminates
- Has its own private memory space
 - not accessible by other processes; not even other instances of the same program

What does UNIX give a process?

- A table of environment variables
 - just a bunch of `name=value` settings
 - kept in memory (process gets own private copy)
- A table of open files
 - 0: standard input
 - 1: standard output
 - 2: standard error
- A set of argument strings
 - e.g. what you put after the command name

The shell: a simple interface

- The shell lets you start processes
 - and waits for them to finish, unless you run them in the "background"
- The shell lets you set environment variables
- The shell lets you set up file descriptors
 - Normally stdin is connected to your keyboard and stdout/stderr to your screen, but you can override

The shell lets you pass arguments

Shell expansion

- The shell performs processing on your command line before starting the program
 - Splits line into words (cmd, arg1, arg2, ...)
 - Searches for cmd in PATH if required
 - Performs various types of argument expansion
-
- See exercise

The shell itself runs as a process

- A shell can start another shell
- A shell has its own environment
 - e.g. it uses the PATH setting to locate programs
 - it copies the environment to its children
- A shell has stdin/stdout/stderr
 - You can run a non-interactive shell, i.e. a script
 - Examples include periodic system tidying
 - log rotation

How are new processes started ?

- The current processes "clones" itself via the `fork()` call
- The fork'ed copy is called the child
 - it shares all the characteristics of the parent, including memory, open files, etc...
- The child replaces itself by calling the new program to be run via `exec()`

|
`fork()`

/ \

parent child

Once a process has started...

- It can make "system calls" to the Kernel as needed, e.g. to
 - read and write data
 - open and close files
 - start new child processes (known as "fork")
 - ...etc
- Using its pid, you can send it a "signal", e.g.
 - Request to terminate
 - Request to suspend (stop temporarily)
 - or restart

Process control from the shell

- For a "foreground" process
 - Ctrl-C = terminate
 - Ctrl-Z = suspend **
- Show all processes
 - ps auxw
- Send a signal to any process
 - kill [-sig] pid
- More advanced job control
 - jobs = list all jobs (children) started by this shell
 - fg %n = resume in foreground **

Summary

- Processes identified by pid
- Each process at start gets 3 things:
 - Environment variables, e.g.
HOME = "/home/you"
 - Open files
 - Arguments
- You can send signals to a running process
- At end it returns a numeric exit

Practical Exercise 1



Processes and security

- Each process runs with set privileges
 - effective uid
 - effective gid
 - supplementary groups
- Some operations are only available to root
 - e.g. bind socket to port below 1024
 - e.g. shut down system
- A process running as root (euid=0)
can choose to run as other uid but

How do users change passwords?

- Note that `/etc/master.passwd` is only readable and writable by root
- The 'passwd' program has special privileges, it is marked "setuid root"
- Whenever a user starts the 'passwd' program, kernel gives it `ewid= root`
 - It can then change the user's password

A side...

- It's really useful to think of commands in pairs
 - The command which shows a setting and the command which changes that setting
 - Example:
 - pwd shows the current working directory
 - cd changes the current working directory
-
- Follow the 3-step system for

Commands for managing files

- Show which files exist: `ls`
 - Show detail (long form): `ls -l`
 - Manipulating files: `cp`, `mv`, `rm`
 - Which editor to use?
 - `vi`
 - clunky but always available
 - `ee`
 - FreeBSD specific
 - `joe`
 - has to be installed as a separate package
-
-

The Virtual Filesystem (VFS)

- All filesystems appear in a single tree
 - Must have a root device — /
 - Can attach other devices at other points
 - At bootup, everything in /etc/fstab is mounted
 - except lines marked 'noauto'
-
-

Key VFS commands

- Show status
 - mount
 - df
- Attach device
 - mount -t cd9660 /dev/acd0 /cdrom
 - /cdrom is called the "mount point"
 - it's just an empty subdirectory
 - after mounting, the filesystem contents appear here
- Detach device
 - ~~umount /cdrom~~

Other devices

- Formatting a floppy disk
 - `fdformat /dev/fd0`
 - `newfs_msdos -L myfloppy /dev/fd0`
- Mounting a floppy disk
 - `mount -t msdos /dev/fd0 /mnt`
- USB pen
 - `mount -t msdos /dev/das1 /mnt`
 - typical example
 - look in `/var/log/messages` to check device
 - use `'fdisk /dev/das1'` to look at slices

Filesystem safety

- DON'T remove any media until it has been unmounted
 - Otherwise, filesystem can be corrupted
 - Kernel won't let you unmount a filesystem if it is in use
 - Use 'fstat' to find processes using it
 - ALWAYS shut down properly
 - Filesystem repair tool is called "fsck"
-
-

Use root sparingly

Unless you must, do not use the root user for day-to-day activities. It is easier to break things that way. Only use root, if you must.

A Tour of UNIX

...looking a bit closer under the
hood



Processes

- A running instance of a program is called a "process"
- Identified by a numeric process id (pid)
 - Pid is unique while process is running; will be re-used some time after it terminates
- Has its own private memory space
 - not accessible by other processes; not even other instances of the same process

What does UNIX give a process?

- A table of environment variables
 - just a bunch of `name=value` settings
 - kept in memory (process gets own private copy)
- A table of open files
 - 0: standard input
 - 1: standard output
 - 2: standard error
- A set of argument strings
 - e.g. what you put after the command
name

The shell: a simple interface

- The shell lets you start processes
 - and waits for them to finish, unless you run them in the "background"
- The shell lets you set environment variables
- The shell lets you set up file descriptors
 - Normally stdin is connected to your keyboard and stdout/stderr to your screen, but you can override

The shell lets you set up file descriptors

Shell expansion

- The shell performs processing on your command line before starting the program
 - Splits line into words (cmd, arg1, arg2, ...)
 - Searches for cmd in PATH if required
 - Performs various types of argument expansion
-
-
- See exercise

The shell itself runs as a process

- A shell can start another shell
- A shell has its own environment
 - e.g. it uses the PATH setting to locate programs
 - it copies the environment to its children
- A shell has stdin/stdout/stderr
 - You can run a non-interactive shell, i.e. a script
 - Examples include periodic system tidying
 - log rotation

How are new processes started ?

- The current processes "clones" itself via the `fork()` call
- The fork'ed copy is called the child
 - it shares all the characteristics of the parent, including memory, open files, etc...
- The child replaces itself by calling the new program to be run via `exec()`

|
fork()

/ \

parent child

Once a process has started...

- It can make "system calls" to the Kernel as needed, e.g. to
 - read and write data
 - open and close files
 - start new child processes (known as "fork")
 - ...etc
- Using its pid, you can send it a "signal", e.g.
 - Request to terminate
 - Request to suspend (stop temporarily)
 - or restart

Process control from the shell

- For a "foreground" process
 - Ctrl-C = terminate
 - Ctrl-Z = suspend **
- Show all processes
 - ps auxw
- Send a signal to any process
 - kill [-sig] pid
- More advanced job control
 - jobs = list all jobs (children) started by this shell
 - fg %n = resume in foreground **

Summary

- Processes identified by pid
- Each process at start gets 3 things:
 - Environment variables, e.g.
HOME = "/home/you"
 - Open files
 - Arguments
- You can send signals to a running process
- ~~At end it returns a numeric exit~~

Practical Exercise 1

Processes and security

- Each process runs with set privileges
 - effective uid
 - effective gid
 - supplementary groups
- Some operations are only available to root
 - e.g. bind socket to port below 1024
 - e.g. shut down system
- A process running as root (euid=0)
can change to any other uid but

How do users change passwords?

- Note that `/etc/master.passwd` is only readable and writable by root
- The 'passwd' program has special privileges, it is marked "setuid root"
- Whenever a user starts the 'passwd' program, kernel gives it `uid = root`
 - It can then change the user's ~~password~~

Aside...

- It's really useful to think of commands in pairs
 - The command which *shows* a setting and the command which *changes* that setting
- Example:
 - pwd shows the current working directory
 - cd changes the current working directory
- Follow the 3-step system for

Commands for managing files

- Show which files exist: `ls`
 - Show detail (long form): `ls -l`
 - Manipulating files: `cp`, `mv`, `rm`
 - Which editor to use?
 - `vi`
 - chunky but always available
 - `ee`
 - FreeBSD-specific
 - `joe`
 - has to be installed as a separate package
-
-

The Virtual Filesystem (VFS)

- All filesystems appear in a single tree
 - Must have a root device — /
 - Can attach other devices at other points
 - At bootup, everything in /etc/fstab is mounted
 - except lines marked 'noauto'
-
-

Key VFS commands

- Show status
 - mount
 - df
- Attach device
 - mount -t cd9660 /dev/acd0 /cdrom
 - /cdrom is called the "mount point"
 - it's just an empty subdirectory
 - after mounting, the filesystem contents appear here
- Detach device
 - ~~umount /cdrom~~

Other devices

- Formatting a floppy disk
 - `fdformat /dev/fd0`
 - `newfs_msdos` → `myfloppy /dev/fd0`
- Mounting a floppy disk
 - `mount -t msdos /dev/fd0 /mnt`
- USB pen
 - `mount -t msdos /dev/das1 /mnt`
 - typical example
 - look in `/var/log/messages` to check device
 - use `'fdisk /dev/das'` to look at slices

Filesystem safety

- DON'T remove any media until it has been unmounted
 - Otherwise, filesystem can be corrupted
 - Kernel won't let you unmount a filesystem if it is in use
 - Use 'fstat' to find processes using it
 - ALWAYS shut down properly
 - Filesystem repair tool is called "fsck"
-
-

Use root sparingly

Unless you must, do not use the root user for day-to-day activities. It is easier to break things that way. Only use root, if you must.
