

Exercise 2.3: Building a DNS cache

0. Become the Root User

For these exercises we will run as the root user. In order to become root on your machine do:

```
$ sudo bash
```

and your prompt should change to a "#".

1. Check if BIND is installed

```
$ dpkg --get-selections | grep bind
```

If you do not see a `_complete_` list like this:

bind9	install
bind9-host	install
bind9utils	install
libbind-confparser-perl	install
libbind9-60	install

Then bind9 is not fully installed. The package "bind9" is the critical item.

For more details type about bind you can type:

```
$ aptitude show bind9
```

2. Install Bind version 9

```
# apt-get install bind9
```

Check the version of BIND which is installed

```
# named -v  
BIND 9.7.0-P1
```

3. Check if BIND is running

Run these commands:

```
# ps aux | grep named  
# grep bind /var/log/syslog  
# service bind9 status
```

4. Reconfigure your resolver to use your own cache only

Edit `/etc/resolv.conf` as follows:

```
search ws.nsrc.org  
nameserver 127.0.0.1
```

Remove any existing 'nameserver' lines, or comment them out by inserting '#' at the front. 127.0.0.1 is the loopback address; that is, an IP address which means 'send the packet to myself'.

Notice that after you do this attempts to use the classroom namespace will fail. For instance try:

```
# ping pc10.ws.nsrc.org
```

We will fix this in exercise 7.

5. Opening BIND to external requests

```
# vi /etc/bind/named.conf.options
```

In the file add the following lines under the options

```
recursion yes;
allow-recursion { any; };
listen-on      { any; };
```

Save the file and restart bind

```
# service bind9 stop
# service bind9 start
```

5. Send some queries

Issue a query. Make a note of whether the response has the 'aa' flag set. Look at the answer section and note the TTL of the answer. Also note how long the query took to process.

Then repeat the `_exact same_` query, and note the information again.

```
$ dig www.tiscali.co.uk. Does it have the 'aa' flag? _____
                        What is the TTL of the answer? _____ seconds
                        How long is the Query Time? _____
                        milliseconds

$ dig www.tiscali.co.uk. Does it have the 'aa' flag? _____
                        What is the TTL of the answer? _____ seconds
                        How long is the Query Time? _____
                        milliseconds
```

Repeat it a third time. Can you explain the differences?

If your neighbour has got their cache working, then try sending some queries to their cache (remember ``dig @x.x.x.x ...``)

6. Watch the cache in operation

You can take a snapshot of the cache contents like this:

```
# /usr/sbin/rndc dumpdb
# less /var/cache/bind/named_dump.db
```

(Don't do this on a busy cache – you will generate a huge dump file!)

You can watch the cache making queries to the outside world using ``tcpdump`` in a different window

```
# tcpdump -n -s1500 -i eth0 udp port 53
```

While `tcpdump` is running, in the first window flush your cache (so it forgets all existing data) and then issue some queries.

```
# rndc flush
# dig www.tiscali.co.uk. -- and watch tcpdump output. What do you see?
# dig www.tiscali.co.uk. -- watch tcpdump again. This time?
```

7. Using a Forwarding Name Server

Try querying the DNS for one of our workshop machines:

```
# pc.ws.nsrc.org
```

You should receive an ANSWER: 0 response (i.e. it fails).

The Authoritative Name Server for our class DNS name space (ws.nsrc.org) is located at 10.10.0.241. Since we have updated your /etc/resolv.conf file to no longer use this name server queries for the domain ws.nsrc.org we need to tell our caching name server to use 10.10.0.241 as a forwarding name server. This means we'll make all our DNS requests to this server, but we'll still be caching the results locally. To do this do:

```
# vi /etc/bind/named.conf.options
```

And replace the section that looks like:

```
// forwarders {  
//     0.0.0.0;  
// };
```

With:

```
forwarders {  
    10.10.0.241;  
};
```

Save the file and restart bind:

```
# service bind9 restart
```

Now trying querying again:

```
# dig pc1.ws.nsrc.org
```

And you should get a proper response.

8. Tightening up the configuration (optional)

Following the examples on the presentation, create zonefiles which map localhost to 127.0.0.1 and 127.0.0.1 to localhost, and test.

Following the examples on the presentation, create an acl which restricts access to your cache to your machine only. Get someone else to try to resolve names using your cache. Remember:

```
rndc reload          # to make your modified configuration active  
tail /var/log/syslog  # to check for errors in your configuration
```