Campus Network Best Practices: IP Addressing

Dale Smith Network Startup Resource Center dsmith@nsrc.org

This document is a result of work by the Network Startup Resource Center (NSRC at http://www.nsrc.org). This document may be freely copied, modified, and otherwise re-used on the condition that any re-use acknowledge the NSRC as the original source.





Who Needs Public IP Space?

- Every campus must have Public IP address space
 - Where do you get it?
- A REN needs must have IP address space
- If the REN becomes ISP, it must have address space for its "customers"
- Any University can get their own IP address space that is independent of the ISP





Provider Independent IP Addresses

- What are provider independent IP addresses?
 - Public IP addresses that are not allocated to you by your Internet Service Provider.
- Can move between service providers without changing IP addresses
- If your REN gets space, then addresses provided to you by your REN is not provider independent





NAT is a reality

- NAT is common technique to reduce number of public IP addresses required
- NAT makes some things hard
 - NAT breaks some things
 - SIP (standard-based VoIP)
 - H.323 Video Conferencing
 - Makes it harder to track down viruses and hackers





Who Needs Provider independent IP and ASN?

- REN
 - Must have both ASN and Provider Independent IP
- Campus Network
 - All campuses must have Public IP, doesn't have to be provider independent
 - Only need ASN if campus is multi-homed
- How much IP address space?





General Notes on IP Addressing

- IP version 4 addresses are 32 bits long
- IP address blocks allocated in powers of 2
 - Blocks of addresses: 1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, 2048, 4096, etc.
- CIDR notation: Address blocks are described with a notation of /number. /32 = 1 address, /31 = 2, /30 = 4, /24 = 256




Campus Network IP Addressing

- Build a spreadsheet
 - One row for every building on your campus
 - Write down how many computers will be in each building
 - Round up to the nearest power of 2
 - Add a row for servers
 - Add a row for wireless





A Simple Campus Example







A Simple Campus Example

| Building | Hosts | CIDR Block | Size | Total |
|-------------------------|-------|------------|------|-------|
| Administration Building | 68 | /25 | 128 | 128 |
| Physics Building | 220 | /24 | 256 | 256 |
| Chemistry Building | 120 | /24 | 256 | 256 |
| Computer Science | 200 | /24 | 256 | 256 |
| Literature Building | 44 | /26 | 64 | 64 |
| Server Network | 20 | /27 | 32 | 32 |
| Wireless Network | 300 | /23 | 512 | 512 |
| Total | | | | 1504 |

Round 1504 up to the next CIDR block gives you 2048 or a /21 Note: this doesn't provide for any expansion of number of networks





Questions?

This document is a result of work by the Network Startup Resource Center (NSRC at http://www.nsrc.org). This document may be freely copied, modified, and otherwise re-used on the condition that any re-use acknowledge the NSRC as the original source.



