

# r1-ixp6-isp1 config

```
hostname r1-isp6-ixp1
!
aaa new-model
aaa authentication login default local
aaa authentication enable default enable
aaa session-id common
!
!
no logging console
logging buffered 8192 debugging
ipv6 unicast-routing
no ip domain-lookup

username isplab secret lab-PW
enable secret lab-PW
service password-encryption

interface FastEthernet0/0
description IXP
ip address 192.168.1.6 255.255.255.0
ipv6 address fd90:192:168:1::6/64
no shutdown
!
interface FastEthernet0/1
description ISP CORE
ip address 100.66.12.1 255.255.255.240
ipv6 address fd90:100:66:120::1/64
no shutdown
!
access-list 99 permit 100.66.13.10
snmp-server community NetManage ro 99
snmp-server ifindex persist

line con 0
exec-timeout 0 0
transport preferred none
stopbits 1
line aux 0
exec-timeout 0 0
transport preferred none
stopbits 1
line vty 0 4
exec-timeout 0 0
transport preferred none
```

```
!
!
end
```

From:  
<https://wiki.lpnz.org/> - Workshops

Permanent link:  
<https://wiki.lpnz.org/doku.php?id=2015:pacnog17-ws:track1:r1-isp6-ixp1-cfg>



Last update: **2015/06/29 05:20**