


DNS/DNSSEC Workshop


TSIG

This document is a result of work by the Network Startup Resource Center (NSRC at <http://www.nsrc.org>). This document may be freely copied, modified, and otherwise re-used on the condition that any re-use acknowledge the NSRC as the original source.


DNS: Data Flow



DNS Vulnerabilities



TSIG protected vulnerabilities




What is TSIG?

- **Transaction SIGnature**
 - A mechanism for protecting communication between name servers and between stub resolvers and nameservers
- A keyed-hash is applied (like a digital signature), so the recipient of the message can verify that it hasn't been tampered with:
 - DNS question / answer
 - timestamp
- Based on a shared secret
 - Both the sender and recipient must be configured with it
 - ACLs
 - In some contexts, names of keys (more on this later)

What is TSIG?

- RFC 2845 – TSIG
- Can also be used to authorize:
 - zone transfers
 - dynamic updates
 - authentication of caching forwarders
- Used in server configuration – not in the zone file

TSIG example



TSIG steps

- Generate secret
- Communicate secret
- Configure servers
- Test

TSIG – Names & Secrets

- TSIG name
 - A name is given to the key. The name is what is transmitted in the message (so the receiver knows what key the sender has used, out of possibly many)
- TSIG secret value
 - A value determined during key generation
 - Usually seen encoded in BASE64

TSIG – Generating a Secret

- dnssec-keygen
 - Simple tool to generate keys
 - Used here to generate TSIG keys
- dnssec-keygen -a <algorithm> -b <bits> -n host <key name>

TSIG – Generating a Secret

- Example:
`dnssec-keygen -a HMAC-MD5 -b 128 -n host ns1-ns2.grp2.net`
- This will generate a key similar to this:
`Kns1-ns2.grp2.net.+157+15921`
- Results in files
`Kns1-ns2.grp2.net.+157+15921.key`
`Kns1-ns2.grp2.net.+157+15921.private`

TSIG – Generating a Secret

- TSIG keys are NEVER put in the zone files
 - There was a KEY Resource Record that was replaced by DNSKEY (for DNSSEC)
 - Could cause some confusion as TSIG keys can look like those KEY RRs:

ns1-ns2.grp2.net. IN KEY 128 157 nEfRx9...bbPn7lyQtE=

TSIG – Generating a Secret

- Configuring the key:
 - in named.conf, same syntax as for the rndc statement:

```
key "ns1-ns2.grp2.net" {  
    algorithm hmac-md5;  
    secret "3etWczaeGesi0cEpeef7PhiKCkgC2sw==";  
};
```

- Using the key:
 - in named.conf, add:

```
server a.b.c.d { key "ns1-ns2.grp2.net"; };
```
- ... where ‘a.b.c.d’ is the IPv4 address of the REMOTE server
 - can use IPv6 address here as an alternative

Configuration example – named.conf

Primary server 10.10.0.1

```
key ns1-ns2.grp2.net {  
    algorithm hmac-md5;  
    secret "APlaceToBe";  
};  
  
server 10.10.0.2 {  
    keys { ns1-ns2.grp2.net; };  
};  
  
zone "my.test.zone" {  
    type master;  
    file "db.myzone";  
    allow-transfer {key ns1-ns2.grp2.net; };  
};
```

Secondary server 10.10.0.2

```
key ns1-ns2.grp2.net {  
    algorithm hmac-md5;  
    secret "APlaceToBe";  
};  
  
server 10.10.0.1 {  
    keys { ns1-ns2.grp2.net; };  
};  
  
zone "my.test.zone" {  
    type slave;  
    file "db.myzone.slave";  
    masters { 10.10.0.1; }; };  
};
```

TSIG – Testing with dig

- You can use dig to check TSIG configuration:

dig @<server> <zone> AXFR –k <TSIG keyfile>

or

dig @<server> <zone> AXFR –y “TSIG secret”

- Wrong key will return “Transfer failed”, and a message will be logged in the security category on the server being queried

TSIG – Time!

- TSIG is time sensitive (to avoid replays)
- message protection expires in 5 minutes
- make sure time is synchronized! (NTP)
- for testing, set the time
- in operations, use NTP!

Questions?

?